Setting up to remotely connect to Raspberry Pi from (Windows) laptop for GWB

NOTE 1: These instructions are primarily meant for Windows computer users. Some instructions and helpful links have been included for Mac and Linux users, but we have not tested all of the steps at those links.

NOTE 2: If you are using the image of the Raspberry Pi provided in the Girls Who Build repository, step 2 has already been done for you. This means that if you try to turn on the Raspberry Pi, if it does not have a network cable plugged in to the network cable port that it will not finish the boot process. If you plan to plug in with a monitor and keyboard to the Raspberry Pi rather than remote-connecting using a laptop/desktop and network connection, you need to reverse Step 2 of these instructions.

- 1. Set the IP address on the laptop you'll be using to interact with the Pi since the laptops' wifi will all be turned off, we'll be setting all of the laptops to 192.168.1.1
 - a. If your computer is a Mac: <u>http://www.macinstruct.com/node/550</u>
 - b. If your computer is running Linux: <u>http://linux-ip.net/html/basic-changing.html</u>
 - c. If your computer is running Windows:
 - Right click on the notification icon for the network in the System Tray and select 'Open Network and Sharing Center'

Troubleshoot problems Open Network and Sharing Center 6/2/2016

ii. In the left panel of the window that that

opens (in Windows 7 and 10, at least) the options will be 'Control Panel Home', 'Change adapter settings,' and 'Change advanced sharing settings' – you want 'Change adapter settings', so click on that.

iii. Right click on 'Wired connection' and select 'Properties' out of the menu that appears. A window like this one will open:

Connect using: Image: Broadcom NetXtreme 57xx Gigabit Controller Configure This connection uses the following items: Image: Client for Microsoft Networks			
Broadcom NetXtreme 57xx Gigabit Controller Configure This connection uses the following items: Client for Microsoft Networks Client for Microsoft Networks Client for Microsoft Networks Client for Microsoft Networks File and Printer Sharing for Microsoft Networks File and Printer Sharing for Microsoft Networks File and Printer Sharing for Microsoft Networks File and Printer Sharing for Microsoft Networks File and Printer Sharing for Microsoft Networks File and Printer Sharing for Microsoft Networks File and Printer Sharing for Microsoft Networks File and Printer Sharing for Microsoft Networks File and Printer Sharing for Microsoft Networks File and Printer Sharing for Microsoft Networks File and Printer Sharing for Microsoft Networks File and Printer Sharing for Microsoft Networks File and Protocol Version 4 (TCP/IPv4) File and Install Install Uninstall Properties Description Transmission Control Protocol/Internet Protocol. The default wide area network protocol that provides communication across diverse interconnected networks	Connect using:		
Configure This connection uses the following items: Image: Client for Microsoft Networks Image: QoS Packet Scheduler Image: QoS Packet Sched	Broadcom Net>	treme 57xx Gigabit Cont	roller
Inis connection uses the following items: Image: Client for Microsoft Networks Image: QoS Packet Scheduler Image: Glient for Microsoft Networks Image: File and Printer Sharing for Microsoft Networks Image: File and Protocol Version 4 (TCP/IPv4) Image: File and Pr			Configure
 Client for Microsoft Networks QoS Packet Scheduler QoS Packet Scheduler File and Printer Sharing for Microsoft Networks Internet Protocol Version 6 (TCP/IPv6) Internet Protocol Version 4 (TCP/IPv4) Internet Protocol Version 4 (TCP/IPv4) Internet Protocol Version 2 (TCP/IPv4) Internet Protocol Version 4 (TCP/IPv4) Internet Protocol Version 2 (TCP/IPv4) Internet Protocol Version 4 (TCP/IPv4) Install Uninstall Properties Description Transmission Control Protocol/Internet Protocol. The default wide area network protocol that provides communication across diverse interconnected networks 	This connection uses	the following items:	
☑ QoS Packet Scheduler ☑ ☑ ☑ ☑ ☑ ▲ Internet Protocol Version 6 (TCP/IPv6) ☑ ▲ Internet Protocol Version 4 (TCP/IPv4) ☑ ▲ Internet Protocol Version 4 (TCP/IPv4) ☑ ▲ Link-Layer Topology Discovery Mapper I/O Driver ☑ ▲ Link-Layer Topology Discovery Responder	Client for Mic	rosoft Networks	
Image: Sile and Printer Sharing for Microsoft Networks Image: Sile and Sharing for Microsoft Networks	QoS Packet	Scheduler	
 Internet Protocol Version 6 (TCP/IPv6) Internet Protocol Version 4 (TCP/IPv4) Link-Layer Topology Discovery Mapper I/O Driver Link-Layer Topology Discovery Responder Install Uninstall Properties Description Transmission Control Protocol/Internet Protocol. The default wide area network protocol that provides communication across diverse interconnected networks 	I File and Print	er Sharing for Microsoft	Networks
✓ Internet Protocol Version 4 (TCP/IPv4) ✓ Link-Layer Topology Discovery Mapper I/O Driver ✓ Link-Layer Topology Discovery Responder ✓ Link-Layer Topology Discovery Responder ✓ Install Uninstall Properties Description Transmission Control Protocol/Internet Protocol. The default wide area network protocol that provides communication across diverse interconnected networks	🗹 📥 Internet Proto	ocol Version 6 (TCP/IPv	6)
 Link-Layer Topology Discovery Mapper I/O Driver Link-Layer Topology Discovery Responder Install Uninstall Properties Description Transmission Control Protocol/Internet Protocol. The default wide area network protocol that provides communication across diverse interconnected networks 			
Link-Layer Topology Discovery Responder Install Uninstall Properties Description Transmission Control Protocol/Internet Protocol. The default wide area network protocol that provides communication across diverse interconnected networks.	🗹 📥 Internet Proto	ocol Version 4 (TCP/IPv	4)
Install Uninstall Properties Description Transmission Control Protocol/Internet Protocol. The default wide area network protocol that provides communication across diverse interconnected networks	 ✓ Internet Prote ✓ Link-Layer Te 	peol Version 4 (TCP/IPv ppology Discovery Mapp	4) ber I/O Driver
Install Uninstall Properties Description Transmission Control Protocol/Internet Protocol. The default wide area network protocol that provides communication across diverse interconnected networks	 ✓ Internet Proto ✓ Link-Layer To ✓ Link-Layer To 	ocol Version 4 (TCP/IPv opology Discovery Mapp opology Discovery Resp	4) ber I/O Driver onder
Description Transmission Control Protocol/Internet Protocol. The default wide area network protocol that provides communication across diverse interconnected networks	 ✓ Internet Proto ✓ ▲ Link-Layer To ✓ ▲ Link-Layer To 	ocol Version 4 (TCP/IPv opology Discovery Mapp opology Discovery Resp	4) er I/O Driver onder
Transmission Control Protocol/Internet Protocol. The default wide area network protocol that provides communication across diverse interconnected networks	 ✓ Internet Proto ✓ Link-Layer To ✓ Link-Layer To 	ocol Version 4 (TCP/IPv opology Discovery Mapp opology Discovery Resp Uninstall	4) er I/O Driver onder Properties
wide area network protocol that provides communication across diverse interconnected networks	 ✓ ▲ Internet Proto ✓ ▲ Link-Layer To ✓ ▲ Link-Layer To Install Description 	ocol Version 4 (TCP/IPv opology Discovery Mapp opology Discovery Resp Uninstall	4) er I/O Driver onder Properties
across diverse interconnected networks	Internet Proto Link-Layer To Link-Layer To Link-Layer To Install Description Transmission Control	opology Discovery Mapp opology Discovery Resp Uninstall	4) over I/O Driver onder Properties
	✓	Decol Version 4 (TCP/IPv popology Discovery Mapp popology Discovery Resp Uninstall DI Protocol/Internet Proto protocol that provides co	A O Driver onder Properties Cool. The default ommunication
	Internet Proto Internet Proto Ink-Layer To Install Description Transmission Contro wide area network across diverse inter	Decol Version 4 (TCP/IPv popology Discovery Mapp popology Discovery Resp Uninstall DI Protocol/Internet Proto protocol that provides co connected networks.	A O Driver onder Properties Cool. The default ommunication
	✓ Internet Proto ✓ Link-Layer To ✓ Link-Layer To ✓ Link-Layer To Install Description Transmission Control wide area network pacross diverse inter	Decol Version 4 (TCP/IPv popology Discovery Mapp popology Discovery Resp Uninstall DI Protocol/Internet Proto protocol that provides co connected networks.	4) ver I/O Driver onder Properties col. The default ommunication

iv. Select 'Internet Protocol Version 4 (TCP/IPv4)' in the list and click on the Properties button immediately below the list

Select 'Use the following IP address' and assign 192.168.1.(something) – as mentioned above, we thought it safest to use 192.168.1.1 since the computers won't be networked to each other. Make sure the subnet mask is 255.255.255.0

General								
You can get IP settings assi this capability. Otherwise, y for the appropriate IP settir	igned autom you need to ngs.	atically ask you	if yo Ir nei	ur n two	netw rk a	ork s dmini	strat	orts or
🔘 Obtain an IP address a	automatically	1						
Ose the following IP ac	ddress:							
IP address:		192.	168	2	1.	1		
Subnet mask:		255 .	255	. 2	55 .	0	1	
Default gateway:		1	<u>n</u>	÷	4	8		
Obtain DNS server add	dress autom	atically						
Use the following DNS	server addr	esses:						
Preferred DNS server:		5.9	1			2		
Alternate DNS server:		×.		÷		0		
Validate settings upor	n exit					Adva	anced	l
		6						

and then click 'OK'

vi. Your computer's wired IP should now be set properly

2. Set up the Raspberry Pi to default to the same IP address every time it turns on

- a. If you have a computer that will recognize the volumes on a Raspberry Pi SD card (Mac or Linux):
 - i. Power off the Raspberry Pi.
 - ii. Remove the SD card and plug into the laptop's card reader
 - iii. Open the Boot volume
 - iv. Open cmdline.txt in a text editor. At the end of the first line add a space followed by 'ip=192.168.1.2'. Do not add any carriage returns.
 - v. Save the file.
 - vi. Unmount all volumes from your computer, remove the SD card, and put back into the Raspberry Pi.
- b. If you have a computer that won't do that, change the file through the Raspberry Pi:

SEE NOTE 2 at the beginning of this document.

- If you are doing the GWB camera exercise, you will have a touch screen LCD that you can plug in to the Raspberry Pi. Or you could use some other monitor. You will also need a USB keyboard and will likely want a mouse, even if you're using the touch screen LCD.
- ii. Connect the monitor, keyboard, and mouse. Turn on the Raspberry Pi.
- iii. Open the Terminal. (In the OS we were using: Menu > Accessories > Terminal)
- iv. Type in sudo nano /boot/cmdline.txt to edit the cmdline.txt file
- v. At the end of the line add a space and 'ip=192.168.1.2' Do not add any carriage returns/new lines.
- vi. Hit Ctrl-O to save the change
- vii. Hit enter to save as the same filename
- viii. Hit Ctrl-X to exit nano
- 3. Connect a standard network cable between the laptop you set the IP address on earlier and the Raspberry Pi. This must be done every time the Raspberry Pi boots, but it does not need to stay plugged in.
- 4. Connect to the Raspberry Pi from the laptop you have two options, and may want to play with both. The first time you make a new connection, either using the command line (SSH) or remote desktop, it will ask you if you want to trust the connection. Since you have set up the connection to directly connect to the Raspberry Pi that you set up, this should be an easy "yes."
 - a. Option 1: SSH into the Raspberry Pi from the laptop this means using a command line interface for the connection.
 - i. If you are using a Mac or Linux Machine:
 - 1. Open a terminal
 - 2. Enter 'ssh pi@192.168.1.2'
 - 3. Enter the password ('raspberry')
 - 4. Congrats, you're in! Proceed with the exercise.
 - ii. If you are using a Windows Machine:
 - 1. Install Putty
 - a. Current download link is http://www.chiark.greenend.org.uk/~sgtatham/putty/download.html
 - b. Save putty.exe to the desktop or somewhere else you will find it easily.
 - 2. Open Putty
 - 3. Set up the session (figure on next page)
 - a. Host Name (or IP address) set as 192.168.1.2
 - b. Leave the Port as it defaults to, or set to 22. I don't know.
 - c. Connection Type needs to be SSH
 - d. Suggest saving session as 'Camera' by entering 'Camera' and clicking 'Save' in the 'Load, Save, or delete a stored session' section before the next step
 - e. Click on 'Open' or double click on 'Camera' if you chose to save the session that way
 - f. If you save the session, next time you can just double click on the name you saved the session as.
 - 4. It will ask you for a username. Enter 'pi' (visual needed)

Session	Basic options for your PuTTY session				
Logging	Specify the destination you want to connect to				
Terminal Keyboard	Host Name (or IP address)	Port			
Bell	192.168.1.2	22			
- Features - Window - Appearance - Behaviour - Translation - Selection - Colours	Connection type: Raw Telnet Rlogin SSH Serial				
	Load, save or delete a stored session Saved Sessions				
	Camera				
	Default Settings	Load			
Data		Court			
- Proxy - Telnet - Rlogin ⊕ SSH - Serial		Save			
		Delete			
	Close window on exit: Always Never Only on	clean exit			

This is an example of what you should enter in to the window for PuTTy if you are trying to use SSH to connect to the Raspberry Pi.

Note how we are suggesting that you save the session as "Camera" before clicking "Open" the first time.

If you do save the session, the next time you open PuTTy you can simply double click on 'Camera' in the list of saved sessions to connect to the Rasperry Pi.

- 5. It will ask you for a password. Enter 'raspberry'
- 6. Congratulations, you are logged on!
- b. Option 2: Use a Remote Desktop application benefits: you can use the mouse and file explorer (and any other apps not based on the command line) on the Raspberry Pi.
 - i. If you are using a Mac or Linux Machine:
 - 1. Google for a solution. Suggestions that were found when we looked were VNC or the Windows Remote Desktop app for Mac. (sorry we are not more helpful)
 - ii. If you are using a Windows Machine
 - 1. If you used the GWB Raspberry Pi image, you can use the Windows Remote Desktop Connection application. If you did not, then look into how to properly set up the Raspberry Pi to support Windows Remote Desktop Connection.

2. On the PC, open Remote Destop Connection.

😼 Remote D	esktop Connection		
-	Remote Desktop Connection		
Computer:	192.168.1.2	¥	
User name:	None specified		
You will be a	sked for credentials when you connect.		
Show C	Options Co	onnect Help	

- 3. Enter 192.168.1.2 as the Computer to connect to (as shown above)
- 4. Optionally, you can save this connection with the username. We recommend it! Select "Show Options" to be shown the following screen:

	Remote Conn	e Desk ectio	n					
eneral	Display Local	Resources	Programs	Experience	Advanced			
Logon	settings							
1	Enter the nar	ne <mark>o</mark> f the rer	note comput	er.				
20	Computer:	192.168.	1.2					
	User name:	pi						
	You will be a	You will be asked for credentials when you connect.						
	Allow me	to save <mark>crec</mark>	lentials					
Connec	ction settings							
	Save the cur saved conne	rent connec ction.	tion settings	to an RDP file	e or open a			
	Save		Save As		Open			

Then enter 192.168.1.2 as the Computer, 'pi' as the username (as shown) Then click

the "Save As" button. We recommend saving as "Camera.rdp" on the desktop. Then you can double click on the Camera.rdp icon on the Windows desktop to connect to the Raspberry Pi rather than typing in the IP address again for future connections.

- 5. Whether you completed step 4 or not, either double click on your saved connection or click "Connect" on the Remote Desktop Connection window. If you did not save your session or saved your session without a username, it will as you for a username. This is 'pi'. (no quotes) Then it will ask you for a password. This is 'raspberry' (again, no quotes)
- 6. Congratulations, you are connected!

Resource: Girls Who Build Cameras Kristen Railey

The following may not correspond to a particular course on MIT OpenCourseWare, but has been provided by the author as an individual learning resource.

For information about citing these materials or our Terms of Use, visit: https://ocw.mit.edu/terms.

Resource: Girls Who Build Cameras

Kristen Railey, Bob Schulein, Olivia Glennon, Leslie Watkins, Alex Lorman, Carol Carveth, and Sara James

The following may not correspond to a particular course on MIT OpenCourseWare, but has been provided by the author as an individual learning resource.

For information about citing these materials or our Terms of Use, visit: https://ocw.mit.edu/terms.